

**CERTIFIED LAND CORNER RECORDATION**

(REFERENCE FSH 5681.65)

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found-stone as per record, no bearing trees found.

Record: Set a granite stone, 18 inches x 14 inches x 6 inches,  
12 inches in the ground, for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on  
North face.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1973

Set a  $1\frac{1}{2}$ " I.D. x 30" galvanized iron pipe 20 inches in ground,  
stamped as shown below from which an 8 inch Douglas Fir bears  
North  $10^{\circ}$  West 26.8 feet distance; a 6 inch Lodgepole Pine bears  
South  $6^{\circ}$  West 8.8 feet distance.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal

I, .....  
certify that the information shown herein is true and  
correct.


Signature of Ground Party Chief

I, J. T. Shaw  
certify that I have carefully performed or reviewed the  
work done on the diagrammed corner as reported on this  
recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

N.



= Corner recorded on the sheet

2343-S  
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4<sup>th</sup> day of February 1974, was noted on the cross-index plat and is  
assigned page No. 330, in book No. 1

Eleanor L. Vaughn, Mae Watson, Deputy  
County Official

Cross Index No. R. 11 T. 33 N. R. 31 W. P. Mer.

100  
100  
100  
100  
100