

**CERTIFIED LAND CORNER RECORDATION**  
(REFERENCE FSH 5681.65)

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No evidence of corner found. See plat of Pipe Creek properties for proportionate location.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1973

Set a 1½" I.D. x 30" galvanized iron pipe 20 inches in ground, stamped as shown below, from which an 8 inch Lodgepole Pine scribed RM bears North 62° West 28.9 feet distance; an 8 inch Lodgepole scribed RM bears North 3° East 12.9 feet distance; a 6 inch Lodgepole scribed RM bears South 38° East 31.10 feet distance; a 6 inch Lodgepole Pine bears South 58° West 13.2 feet distance.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal

I, \_\_\_\_\_  
certify that the information shown herein is true and correct.


Signature of Ground Party Chief

I, J. T. Shaw  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

N.



= Corner recorded on the sheet

2343-S  
Registration NumberOffice of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of February 1974, was noted on the cross-index plat and is assigned page No. 331, in book No. 1

Eleanor L. Vaughn Mae Watson Deputy  
County Official

Cross Index No. R 9 T. 33 N R. 31 W P. Mer.

