

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1973

Set 1½" I.D. x 30" galvanized iron pipe 20 inches into the ground stamped as shown below, from which an 8" Lodgepole Pine bears South 27° West 15.5 feet distance scribed RM 1; an 8" Lodgepole Pine bears North 54° West 9.2 feet distance, scribed RM 2.

Distance to center of tree.

Declination 22° East.

All trees have bearing tree tags.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal

I, \_\_\_\_\_  
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, J. T. Shaw  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

2343-S  
Registration Number

DIAGRAM OF CORNER:

N.

See back of this sheet for index to corners.

1 = Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of February 1974, was noted on the cross-index plat and is assigned page No. 332, in book No. 1 Eleanor L. Vaughn, MacCistear, Deputy County Official

SEC 28 T33N R31W

