

# CERTIFIED LAND CORNER RECORDATION

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.


## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1973

Set 1½" I.D. "x 30" galvanized iron pipe 26 inches in the ground stamped as shown below, from which a 6 inch Lodgepole Pine bears North 28° East 16.9 feet distance scribed RM 1; a 10 inch Lodgepole Pine bears South 80° East 12.3 feet distance scribed RM 2.

Distance to center of tree.  
Declination 22° East.  
All trees have bearing tree tags.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal

I, \_\_\_\_\_  
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, J. T. Shaw  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

2343-S  
Registration Number

DIAGRAM OF CORNER:

N.  
See back of U ½  
11 ½ for index  
of corners.

2 = Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln  
This "corner record" was filed for record on the 4th day of February 1974, was noted on the cross-index plat and is assigned page No. 333, in book No. 1 Eleanor L. Laughlin, Reg. M. Watson, Deputy  
County Official

SEC 28 T33N R31W

