

# CERTIFIED LAND CORNER RECORDATION

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.

## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1973

Set  $1\frac{1}{2}$ " I.D. x 30" brass capped galvanized iron pipe 26 inch in ground stamped as shown below, from which an 8 inch Lodgepole Pine bears North  $82^{\circ}$  East 2.8 feet distance scribed RM 1; an 8 inch Lodgepole Pine bears South  $18^{\circ}$  East 8.4 feet distance scribed RM 2.

Distance to center of tree.

Declination  $22^{\circ}$  East.

All trees have bearing tree tags.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal

I, \_\_\_\_\_  
certify that the information shown herein is true and correct.

\_\_\_\_\_  
Signature of Ground Party Chief

I, J. T. Shaw  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

J. T. Shaw  
Signature of Surveyor

2343-S  
Registration Number

DIAGRAM OF CORNER:

N.  
See back of U  $\frac{1}{2}$   
11  $\frac{1}{2}$  for index  
of corners.

5 = Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln  
This "corner record" was filed for record on the 4<sup>th</sup> day of February 1974, was noted on the cross-index plat and is assigned page No. 336, in book No. 1 Eleanor L. Laughon, Mae Watson, Deputy  
County Official

