CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1973

Set $1\frac{1}{2}$ " I.D. x 30" galvanized iron pipe 18 inches in ground stamped as shown below, from which an 8 inch Lodgepole Pine bears North 56° East 21.1 feet distance scribed RM 1; A 10 inch Lodgepole Pine bears South 12° East 10.5 feet distance scribed RM 2.

Distance to center of tree. Declination 22° East. All trees have bearing tree tags.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



		<u> </u>	
Surveyor's Seal	т	j j	DIAGRAM OF CORNER:
	certify that the information shown herein is trecorrect.	ue and	N. See back of U ½ 11 ½ for index
	Signature of Ground Party Chief	ė i	of corners.
	I, J. T. Shaw certify that I have carefully performed or review	ved the	
	work done on the diagrammed corner as reported recordation form and approve the same.	on this	.O = Corner recorded on the sheet
	Signature of Surveyor 2343-5 Registration N		
Office of Clerk and Recorder, Co	unty of Lincoln	r a	
	1 Th 2/1	711	***************************************
This "corner record" was filed for	or record on the day of laruary 15	/, wa	s noted on the cross-index plat and is

assigned page No. 341, in book No.

County Official

Cross Index No. 55-10 T. 33 N R. 31 W. P. Mer.

•