

CERTIFIED LAND CORNER RECORDATION  
(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.


DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set a 1½" I.D. x 30" galvanized pipe 24 inches into ground stamped as shown below, from which an 8 inch Lodgepole Pine, scribed RM 1, bears North 14° East 34.8 feet distance; an 8 inch Lodgepole Pine, scribed RM 2, bears North 70° East 41.6 feet distance.

Date of work: Nov. 1973

Distance to center of tree.  
Declination 22° East.  
All trees have bearing tree tags.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal

I, \_\_\_\_\_  
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, J. T. Shaw  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

J. T. Shaw  
Signature of Surveyor

DIAGRAM OF CORNER:

N. See back of U 1/2  
11 1/2 for index  
of corners.

11 = Corner recorded on the sheet

2343-S  
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of February 1974, was noted on the cross-index plat and is assigned page No. 342, in book No. 1

Eleanor L. Vaughn, Mac Watson, Deputy  
County Official

Cross Index No. S 1/2 11 T. 33 N R. 31 W P. Mer.

