

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1973


Set a 1½" I.D. x 30" brass capped galvanized iron pipe 24 inches into ground, stamped as shown below, from which an 8 inch Lodgepole Pine bears West 17.7 feet distance, scribed RM 1; a 9 inch Lodgepole Pine scribed RM 2 bears North 5° West 16.1 feet distance.

Both trees tagged.

Distance to center of tree.

Declination 22° East.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, J. T. Shaw
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

N.
See back of U ½
11 ½ for index
of corners.

12= Corner recorded on the sheet

2343-S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of February, 1974, was noted on the cross-index plat and is assigned page No. 343, in book No. 1. Eleanor L. Clough, Deputy County Official

