

**CERTIFIED LAND CORNER RECORDATION**  
(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set a 1½" I.D. x 30" galvanized iron pipe 24 inches into ground stamped as shown below, from which a 16 inch White Pine scribed RM 1 bears South 26° West 12.5 feet distance. A 5 inch Lodgepole Pine bears South 60° East 38 feet distance. Date of work: Nov. 1973

Distance to center of tree.  
Declination 22° East.  
All trees have bearing tree tags.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal

I, \_\_\_\_\_  
certify that the information shown herein is true and correct.

\_\_\_\_\_  
Signature of Ground Party Chief

I, J. T. Shaw  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

J. T. Shaw  
Signature of Surveyor

2343-S  
Registration Number

DIAGRAM OF CORNER:

N.  
See back of U ½  
11 ½ for index  
of corners.

13 = Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4<sup>th</sup> day of February 1974, was noted on the cross-index plat and is assigned page No. 344, in book No. 1

Edward L. Douglas County Official  
Max Watson Deputy  
Cross Index No. 7-12 T. 33 N. R. 31 W. P. Mer.

8.0