

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:


Date of work: Nov. 1973

Set $1\frac{1}{2}$ " I.D. x 30" galvanized iron pipe in rockpile 20 inches in ground, stamped as shown below, from which an 8 inch Lodgepole Pine scribed RM 1 bears South 82° West 39.2 feet distance; a 14 inch Lodgepole Pine bears south 19° East 15.4 feet distance.

Distance to center of tree.
Declination 22° East.

All trees have bearing tree tags.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, J. T. Shaw
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

J. T. Shaw
Signature of Surveyor

DIAGRAM OF CORNER:

N.
See back of U $\frac{1}{2}$
11 $\frac{1}{2}$ for index
of corners.

14 = Corner recorded on the sheet

2343-S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of February 1974, was noted on the cross-index plat and is assigned page No. 345, in book No. 1

Eleanor L. Vaughn
County Official

Cross Index No. 11 1/2 T. 33 N. R. 31 W. P. Mer.

