

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No previous record.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1973


Corner falls in turnout road.

Set 1½" I.D. x 30" galvanized iron pipe one foot below the surface of the road. Set bolt with + chisled in center, from which a 4 inch Lodgepole Pine bears North 4° West 43.7 feet distant scribed RM 1; a six inch Lodgepole bears South 85° East 62.4 feet distant scribed RM 2.

Distance to center of tree. All trees have bearing tree tags.

Declination 22° East.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)



Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, J. T. Shaw
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

2343 S

Registration Number

DIAGRAM OF CORNER:

N.
See back of U ½
11 ½ for index
of corners.

16 = Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of February 1974, was noted on the cross-index plat and is assigned page No. 347, in book No. 1 Eleanor L. Coughlin, Mary Watson, Deputy County Official

