CERTIFIED LAND CORNER RECORDATION

(REFERENCE F3M 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Set for Cor. No. 2. a quartzite stone 24x12x6 ins., 14 ins. in the ground, marked Orig: 2 H.E.S. 414 on SW. face, and a cross(x) on top for the exact corner point, from ·which

Alcross (x) on a larch, 18 ins. dia., bears S.18°50'W., 22 lks. dist.

A cross (x) on a larch, 14 ins. dia., bears N.16°30'W., 25 lks. dist.; each blazed and scribed 2 H.E.S. 414 BT. Raise a mound of earth, 4 ft. base, 2 ft. high, SW. of corner.

Note: Original survey was executed using a 31°06' East declination

Found: Found two larch stumps, one with scribing, at record bearing and distance of described bearing trees. Also found original stone marked as described, lying

on its side, at approximate corner position

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Replaced original stone, firmly in the ground, at exact corner position. Further perpetuated the corner by establishing two new bearing trees.

A 4" fir marked X BT bears S22°30'W 313 links.

A 12" fir marked X 2 BT bears N71°30'W 48 links.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE!)

Surveyor's Seal



Thomas C. Hill Wn. LS 16209 certify that the information shown herein is true and correct.

Signature of Ground Party Chief

Stanley J. Skousen

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

> Stanley J. Skousen Signature of Surveyor

> > 2532-S Registration Number

DIAGRAM OF CORNER:

Date of work: 11-16-/

T33N R33W Sec. H.E.S. 414 Corner #2

> HES # 414

10127

19.28, was noted on the cross-index plat ω This "corner record" was filed for record on the car.a Coral M. Cumming

TUTOR