CERTIFIED LAND CORNER RECORDATION

(REFERENCE | 13H 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) Set for Cor! No. 3, a quartzite stone 24x12x8 ins., 14 ins. in the ground,

marked 3 H.E.S. 414 on NW. face, and a cross (x) on top for the exact corner point, from which

Alcross (x) on a fir 12 ins. dia., bears S.25°40'E, 33 lks. dist.

A cross (x) on a black pine, 8 ins. dia., bears N.4708'E., 3 lks. dist each blazed and scribed 3 H.E.S. 414 BT.

Found:

Found a stone marked as described in good condition, from which a stump hole bea N47°08'E 3 links distant, and a broken fir with legible scribing bears S25°40'E

33 links distant.

The original survey was executed using a 31°06' East; declination. Note:

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

> > Date of work: 11-16-//

Two new bearing trees were established to perpetuate the corner position. A cedar 12" in diameter marked X 3 BT bears S82°20'W 294 links distant.

A:cedar 6" in diameter marked X;BT bears S23-10'E 218 links distant.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



Thomas C. Hill Wn. LS 16209 certify that the information shown herein is true and correct.

Signature of Ground Party Chief


Stanley J. Skousen

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

2532**-**S Registration Number DIAGRAM OF CORNER T33N R33W S.31

H.E.S. 414 Corner #3



Corner recorded on the she

10129

Office of Clerk and Recorder, County of Juncon

This "corner record" was filed for record on the 19. 28 was noted on the cross-index plat T33N

Oval M. Cumming by Bub Colal & Kender