CERTIFIED LAND CORNER RECORDATION (REFERENCE FSM 7153.53) DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) Set a quartzite stone 30x15x10 inches, 20 inches in the ground, marked 1 H.E.S. 414 on SE face, and a cross(x) on top for the exact corner point, from which:

A cross (x) on a fir, 9 inches diameter bears S.57,02'E, 30 links A cross (x) on a cedar 10 inches diameter bears S.02°39'E, 27 links dist.; each blazed and scribed H.E.S. 414 BT. Found stone marked as described, set firmly in the ground in excellent Found: condition, from which; a 5 foot high fir stump marked as described bears S.57°02'E, 30 links dist. and a cedar stump 4 feet high marked as described bears S.02°39'E, 27 links distant. Note: Declination used on the original survey and retracement was 31°06' East. DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER! Date of work:... To perpetuate this corner, the remains of the two bearing trees were marked with metal bearing tree tags. Also scribed a 16" cedar X 1 BT for a new bearing tree, it bears N63° 45'E, 592 links distant. SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



Thomas C. Hill, Wn LS 16209 certify that the information shown herein is true and correct.

Signature of Ground Party Chief

Stanley J. Skousen certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

> Rouser Signature of Surveyor

T33N R33W 530 i H.E.S. 414 'Corner #1 H.E.S. 414

DIAGRAM OF CORNER:

Corner recorded on the shee

10130

Office of Clerk and Recorder, County of Junicols

1920, was noted on the cross-index plat an 53N R33W

Total M. Cummings by Diffs

Charles Kranisch