
INSTRUCTIONS

quent record used to evaluate



Description of monument and accessories set to perpetuate the corner position.

Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

Fill in Cross Index & Section Diagram at bottom of sheet.


CERTIFIED CORNER RECORDATION

Corner S1/16 Sec 17/ Sec 16 T. 33N R. 34W P.M.M. Lincoln County

No record found at Lincoln County Courthouse.

Found a 5/8" rebar and plastic cap JHN 4661S. 2)

3) Replaced plastic cap with a 31/4" aluminum cap, marked as shown:



From which:

An existing 10" Douglas Fir, with scribing scar evident, bears N22°E, 29.5' distant. An existing 17" Cedar, scribed S1/16 S16 BT, bears S84°E, 11.7' distant.

Blazes and scribing were painted red. Bearing tree tags and Land Survey Monument signs were attached to trees. A 6' steel post with Land Survey Monument and Forest Service Property Boundary decals attached was placed $2\frac{1}{2}$ ' south of monument.

		CERTIFICATION
PRIVATE	PRIVATE PRIVATE FIR PRIVATE FIR VIST VIST CEDAR USFS	1, Kevin Todd certify the information shown herein is true and correct. Kown A Todd Signature Ground Party Chief 1, James R. Staples certify that this corner Record correctly represents work performs by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.) Staples Signature of Surveyor & Seal Date: 5-3-99 Reg. No. 1958
	SKETCH OF CORNER	Employer: J.R.S. Surveying, Inc.

ρ , ρ	Sec.	17		
Office of Clerk and Recorder, County of This "corner				
record" was filed for record on				
was noted on the cross-index plat and is assigned page Noin				
book No. 10329 Wal M County Official By PUB				
councy official y				Ĭ

Cross Index No. M-9 T. 33N R. 34W PMM