
INSTRUCTIONS

Original and/or subsequent record used to evaluate the corner position



Description of monument and accessories set to perpetuate the corner position.

Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography tics, position of accessories, etc.

Certification must be signed and scaled by Land Surveyor registered in the State of Montans.
Fill in Cross Index & Section Diagram at bottom of sheet.


CERTIFIED CORNER RECORDATION

Corner C-N-SW-SE1/256 Cor Sec 17 T. 33N R. 34W __P.M.M.<u>Lincoln</u>

No records found at Lincoln County Courthouse

No evidence found on the ground 2)

At the corner position as determined by survey, set a 5/8"x 30" rebar, with a $3\frac{1}{4}"$ aluminum cap marked as shown:



From which:

A 10" Hemlock bears S61°W, 40.2' distant, scribed C N SW SE1/256 S17 BT. A 12" Cedar bears S38°E, 26.4' distant, scribed C N SW SE1/256 S17 BT.

Monument was set 0.2' above grade. A 6' steel post with Land Survey monument and Forest Service Property Boundary decals attached was placed 1.3' south of monument. Blazes and scribing on bearing trees were painted red. Bearing tree tags and Land Survey monument signs were attached to trees.

CERTIFICATION PRIVATE John Marquette James R. Staples B12" CEDAR JAMES R. 10" HEMLOCK **STAPLES** 9958 LS USFS Date: 5-3-99 Reg. No. GISTER SURVE Employer: J.R.S. Surveying, Inc. SKETCH OF CORNER

$\rho \sim \rho$	SE½ S	Sec
Office of Clerk and Recorder, County of Junction. This "corner		
record" was filed for record on		
book Noin the cross-index plat and is assigned page Noin the book Noin the cross-index plat and is assigned page Noin the book Noin the cross-index plat and is assigned page Noin the book Noin the cross-index plat and is assigned page Noin the cross-index plat and index plat and index plat		
county official /		

Cross Index No. M.25-7.5 T. 33N R. 34W PMM