CENTIED CORNER RECORDATION
Corner <u>SE-SE 1/64 S24</u> T. <u>33</u> N., R. <u>34</u> W., P.M.M. <u>Lincoln</u> County
Record:
1970 Section Subdivision by Ninneman Engineering (Book 1 Page 209 Certified Corner Recordation, Lincoln County Records). No monumentation.
Found Evidence :
None
Perpetuation :
The position for the SE-SE 1/64 cor. for Sec. 24 was determined from a closed traverse survey of the SE 1/4 of Sec. 24 by Davis Surveying, Inc. during February of 1999. At the computed position, set a 5/8 inch diam. steel rebar 24 ins. long, 22 ins. in the ground, with a 3 1/4 inch diam. alum. cap marked as shown below, from which:
A Douglas Fir 11 ins. diam. bears S. 4° W., 10.80 ft. dist., scribed (SE-SE 1/64 S24 BT). A Western Tamarack 9 ½ ins. diam. bears N. 34° W., 11.20 ft. dist., scribed (SE-SE 1/64 S24 BT).
Painted 6 inch wide bands and scribed faces red.
Attached Bearing Tree and Land Survey Monument signs to both trees.
Set a 6 ft. long steel post with Land Survey Monument and Property Line decals 3.00 ft. E. of set monument on line.
SE-SE E4 5 24 Pars-5 dags
Magnetic Declination: 18° E.
CERTIFICATION I, John Damon certify the information shown herein is true and correct Signature of Ground Party Chief I, Ken'E'Davis certify that this Corner ijecord correctly represents work performed by me of under my direction in compliance with the "Corner Recoration Act" 1472-101; pr.seq.; pr. 4 Sketch of Corner Sketch of Corner FIR CERTIFICATION I, John Damon certify the information shown herein is true and correct MAN Davis Signature of Ground Party Chief I, Ken'E'Davis Certify that this Corner ijecord correctly represents work performed by me of under my direction in compliance with the "Corner Recoration Act" Signature of Surveyor & Seal Date of Corner Employer: Davis Surveying, Inc.
Office of Clerk and Recorder, County of Man 24,1999 This "corner record" was filed for record on Man 24,1999 was noted on the cross-index plat and is assigned page No