

CERTIFIED CORNER RECORDATION

CORNER CW1/16 T. 33 N., R. 34 W., P.M.M. LINCOLN COUNTY

RECORD:

NONE

FOUND EVIDENCE:

A 3/4 inch unusable bare rebar no BT's

PERPETUATION:

Set a 5/8 inch dia. rebar capped with a yellow plastic cap stamped K.E.D.
4975-S From which:

A 15 inch DBH Douglas Fir scribed CW 1/16 T33N R34W S24 BT bears
N22°W 20.65 ft dist.

A 7 inch DBH Grand Fir scribed CW1/16 BT bears S87°W 30.60 ft dist.

MAGNETIC DECLINATION: 18° E

15" DOUGLAS
FIR

N 22° W
20.65'

DIAGRAM

K. E. D.

4975-S

S 87° W
30.60'

7" GRAND
FIR



I, KEN DAVIS CERTIFICATION

Certify the information shown herein is true and correct
Signature of Ground Party Chief


I, KENNETH E. DAVIS

certify that this Corner Record correctly represents work
performed by me or under my direction in compliance with the
"Corner Recordation act"
(70-72-101, et seq., M.C.A.)

Signature of Surveyor & Seal

Date: 6/6 Reg. No. 4975-S

Employer: DAVIS Surveying Inc



SKETCH OF CORNER

Office of Clerk and Recorder, County of _____

This "corner" was noted 214780 BOOK: CCR CC&R'S PAGE: 11277 Pages: 1

No. _____ STATE OF MONTANA LINCOLN COUNTY

RECORDED: 10/08/2008 2:15 KOI: CC&R'S


In book No. TAMMY D. LAUER CLERK AND RECORDER

FEE: \$7.00

BY: Jeanne Lauer

TO: FILED

SECTION



Cross Index No. CW1/16 T. 33 N., R. 34 W., P.M.M.

THIS CORNER