I. 1903 C.L.O. Fractional Subdivision and Meanders of T. 33 N. R., 34 W. by Allen B. Benedict granite stone, 21X10X9 ins., 16 ins. in the ground, for 1/4 sec. cor. marked 1/4 on W. face which. A fir, 16 ins. diam, bears N42'30'E, 29 iks. dist., mkd. 1/4 S3 BT. A fir, 24 ins. diam, bears S88'30'W, 28 iks. dist., mkd. 1/4 S4 BT. 1967 B.L.M. Remanumentation by Joseph E. French: The 1/4 sec. cor. of secs. 3 and 4, as determined from the remains of the original bearing trees: A fir, 18 ins. diam, bears N42 1/2'E, 29 iks. dist., mkd. with an ovegrown blaze. A fir snag, 24 ins. diam, bears S88 1/2'W, 28 iks. dist., mkd. 1/4 S4 BT. At the corner point Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. A fir, 8 ins. diam, bears N68 1/2'W, 18 lks. dist., mkd. 1/4 S3 BT. II. Found a 2 in. diam, iron pipe, 6 ins. above the ground, firmly set with a 2 1/2 in. diam. branked as shown above, from which: A fir, 18 ins. diam, bears N68 1/2'W, 18 lks. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2'W, 11.9 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2'W, 11.9 ft. dist., mkd. with a healed face. Monument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS Signature Ground Fary 17-23-16/1. with the forms Records correctly into the formation atoms means is to us a supervision of fire and compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS	
I. 1903 G.L.O. Fractional Subdivision and Meanders of T. 33 N. R. 34 W. by Allen B. Benedict: granite stone, 21X10X9 Ins., 16 ins. In the ground, for 1/4 sec. cor. marked 1/4 on W. face which. A fir, 16 ins. diam, bears N42'30'E, 29 lks. dist., mkd. 1/4 S3 BT. A fir, 24 ins. diam, bears S88'30'W, 28 lks. dist., mkd. 1/4 S4 BT. 1967 B.L.M. Remonumentation by Joseph E. French: The 1/4 sec. cor. of secs. 3 and 4, as determined from the remains of the original bearing trees: A fir, 18 ins. diam, bears N42 1/2E, 29 lks. dist., mkd. with an ovegrown blaze. A fir snag, 24 ins. diam, bears S88 1/2'W, 28 lks. dist., mkd. 1/4 S4 BT. At the corner point Set an iron post, 30 ins. long, 2 1/2 ins. diam,, 24 ins. in the ground, with brass cap mkd. 133N RAW 1/4 S4 S3 1972 from which the new bearing trees: A fir, 8 ins. diam, bears N68 1/2'W, 18 lks. dist., mkd. 1/4 S3 BT. II. Found a 2 in. diam, iron pipe, 6 ins. above the ground, firmly set with a 2 1/2 in. diam. branched as shown above, from which: A fir, 18 ins. diam, bears N68 1/2'W, 11.9 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2'W, 11.9 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2'W, 11.9 ft. dist., mkd. with a healed face. Monument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tope U.S. Forest Service, Supervisions Office, 31374 Hwy, 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Security and Steven A. Boyer 9750LS certify the information shape here in the complex forms of the complex forms and loggers tope U.S. Forest Service, Supervisions Office, 31374 Hwy, 2, Libby, MT 59923 (406) 293-6210 ETCH OF CORNER	County
A fir, 16 ins. diam, bears N42'30'E, 29 lks. dist., mkd. 1/4 S3 BT. A fir, 24 ins. diam, bears S88'30'W, 28 lks. dist., mkd. 1/4 S4 BT. 1967 B.L.M. Remonumentation by Joseph E. French: The 1/4 sec. cor. of secs. 3 and 4, as determined from the remains of the original bearing trees: A fir, 18 ins. diam, bears N42 1/2'E, 29 lks. dist., mkd. with an ovegrown blaze. A fir snag, 24 ins. diam, bears S88 1/2'W, 28 lks. dist., mkd. 1/4 S4 BT. At the corner point Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. A fir, 8 ins. diam, bears N68 1/2'W, 18 lks. dist., mkd. 1/4 S3 BT. II. Found a 2 in. diam, iron pipe, 6 ins. above the ground, firmly set with a 2 1/2 in. diam. branched as shown above, from which: A fir, 18 ins. diam, bears N42 1/2'E, 19.1 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2'W, 11.9 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2'W, 11.9 ft. dist., mkd. with a healed face. III. Pointed red the scribed faces and 6 in. red bands on the bearing trees. Attached Land Sur Manument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby. MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer Signature Ground Party Chief. Signature G	
determined from the remains of the original bearing trees: A fir, 18 ins. diam, bears N42 1/2E, 29 iks. dist., mkd. with an ovegrown blaze. A fir snag, 24 ins. diam, bears S88 1/2W, 28 iks. dist., mkd. 1/4 S4 BT. At the carner point Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. A fir, 8 ins. diam, bears N68 1/2W, 18 iks. dist., mkd. 1/4 S3 BT. II. Found a 2 in. diam. iron pipe, 6 ins. above the ground, firmly set with a 2 1/2 in. diam. branched as shown above, from which: A fir, 18 ins. diam, bears N68 1/2E, 19.1 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2W, 11.9 ft. dist., mkd. with a healed face. III. Painted red the scribed faces and 6 in. red bands on the bearing trees. Attached Land Sur Monument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20 East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisions Office, 31574 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS Specius of Survey and Party Chief Steven A. Boyer 9750LS Specius of Survey and Party Chief Steven A. Boyer 9750LS Specius of Survey and Party Chief Steven A. Boyer 9750LS Specius of Survey and Party Chief Steven A. Boyer 9750LS Specius of Survey and Party Chief Steven A. Boyer 9750LS Specius of Survey County Steven Boyer 9750LS Specius of Survey Steven Boyer 9750LS Specius of Survey Steven Boyer 9750L	
A fir snag, 24 Ins. diam, bears S88 1/2W, 28 lks. dist., mkd. 1/4 S4 BT. At the corner point Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. 133N RAW 1/4 s4	
Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. 133N R34W 1/4 54 53 1972	
from which the new bearing trees: A fir, 8 ins. diam, bears N68 1/2W, 18 lks. dist., mkd. 1/4 S3 BT. II. Found a 2 in. diam. iron pipe, 6 ins. above the ground, firmly set with a 2 1/2 in. diam. br marked as shown above, from which: A fir, 18 ins. diam, bears N42 1/2E, 19.1 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2W, 11.9 ft. dist., mkd. with a healed face. III. Painted red the scribed faces and 6 in. red bands on the bearing trees. Attached Land Sur Monument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293–6211 CERTIFICATION Steven A. Boyer 9750LS early the Information shown haven is true a signature of surveying in sed to the "Corpir Rocker Report Company" in Signature of Surveying is sed to be a signature of Surveying in Scale Company in Signature of Surveying is sed to be a signature of Surveying in Scale Company in Signature of Surveying is sed to be a signature of Surveying in Scale Company in Signature of Surveying is sed to be a signature of Surveying in Scale Company in Signature of Surveying is sed to be a signature of Surveying in Scale Company in Signature of Surveying in Scale Company in	
II. Found a 2 in. diam. iron pipe, 6 ins. above the ground, firmly set with a 2 1/2 in. diam. br marked as shown above, from which: A fir, 18 ins. diam, bears N42 1/2'E, 19.1 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2'W, 11.9 ft. dist., mkd. with a healed face. III. Painted red the scribed faces and 6 in. red bands on the bearing trees. Attached Land Sur Monument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS certify that this Comer Record correctly reference from A Boyer of Surveyor & Seal Signature of Surveyor & Seal Signature of Surveyor & Seal Signature Ground Porty Chief Steven A. Boyer Steven A. Boyer Figure of Surveyor & Seal Signature & & Seal S	
II. Found a 2 in. diam. iron pipe, 6 ins. above the ground, firmly set with a 2 1/2 in. diam. br marked as shown above, from which: A fir, 18 ins. diam, bears N42 1/2E, 19.1 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2W, 11.9 ft. dist., mkd. with a healed face. III. Painted red the scribed faces and 6 in. red bands on the bearing trees. Attached Land Sur Monument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS Certify that the information shown harian is true and the compass of t	
marked as shown above, from which: A fir, 18 ins. diam, bears N42 1/2E, 19.1 ft. dist., mkd. with a healed face. A fir, 10 ins. diam, bears N68 1/2W, 11.9 ft. dist., mkd. with a healed face. III. Painted red the scribed faces and 6 in. red bands on the bearing trees. Attached Land Sur Monument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS certify the Information shown herein is true of the Company of t	
A fir, 10 ins. diam, bears N68 1/2"W, 11.9 ft. dist., mkd. with a healed face. III. Painted red the scribed faces and 6 in. red bands on the bearing trees. Attached Land Sur Monument and Bearing Tree signs. Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS certify the information shown herein is true of surveyor the correction Act 100-52-101 strue of surveyor in Signature Ground Party Chief Secretly that this Corner Record cornectly representation Act 100-52-101 strue of Surveyor in Secretly than the Corner Record cornectly representation Act 100-52-101 strue of Surveyor in Secretly than the Corner Record cornectly representation Act 100-52-101 strue of Surveyor in Secretly than the Corner Record cornectly representation Act 100-52-101 strue of Surveyor in Secretly than the Corner Record cornectly representation and the Corner Rec	ass cap
Date of Fieldwork: 5/13/2008 Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS certify the information shown herein is true or Signature Ground Party Chief Steven A. Boyer certify that this Corner Record correctly represented by the or under my direction. In the Corner Record party Chief Signature of Surveyor & Seal Date: 2/5/2009 Reg. No. 9750LS. Employer: U. S. Forest Services	
Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS certify the information shown herein le true of surveyor at Seal Date: 2/5/2009 Reg. No. 9750LS On the "Compare Record Compatity representation and the "Compare Record Compatity representation	'vey
Survey crew: Steve Boyer Magnetic declination: 20' East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 31374 Hwy. 2, Libby, MT 59923 (406) 293-6211 CERTIFICATION Steven A. Boyer 9750LS certify the information shown herein le true of surveyor at Seal Date: 2/5/2009 Reg. No. 9750LS of the "Cornér Recordation Act-170-722-101" et al. 2015 ETCH OF CORNER NOT TO SCALE Employer: U. S. Forest Securices Sec. 4	
Signature Ground Party Chief Signature Ground Party Chief Steven A. Boyer Signature Ground Party Chief Signature Ground Party Chief Signature Ground Party Chief Signature Ground Party Chief The Corner Record cornectify representation and the Corner Record cornectify representation and the Corner Recordation Act (70-722-10); et al. Signature of Surveyor & Seal Date: 2/5/2009 Reg. No. 97501 Seal Employer: U. S. Forest Service.	·
Signature Ground Party Chief Steven A. Boyer	_
Signature of Surveyor & Seal Date: 2/5/2009 Reg. No. 9750LS A. ETCH OF CORNER NOT TO SCALE Steven A. Boyer cortify that this Comer Record correctly represented by me or under my direction in continuous c	and correct
certify that this Corner Record correctly represented by me or under my direction in continuous content of Surveyor & Sedion in the "Cornér Recordation Act" (70-22-101) et "Signature of Surveyor & Sedion Date: 2/5/2009 Reg. No. 97:50LSA. ETCH OF CORNER NOT TO SCALE Employer: U. S. Forest Service.	COOL
the "Cornér Recordation Act." (70-52-101, et Signature of Surveyor & Seal Date: 2/5/2009 Reg. No. 9750LS O. ETCH OF CORNER NOT TO SCALE Employer: U. S. Forest Securice.	ON TA
Date: 2/5/2009 Reg. No. 9750LS A. ETCH OF CORNER NOT TO SCALE Employer: U. S. Forest Services Sec. 4	
ETCH OF CORNER NOT TO SCALE Employer: U. S. Forest Service. Sec. 4	型OYER 9750L
Lincoln Sec 4	GISTER
Office of Clerk and Recorder, County of Lincoln	SURY
	$\mathcal{D}_{\mathcal{D}}}}}}}}}}$
230209 BOOK: CCR CCER'S PAGE: 11727 Pages: 1 STATE OF MONTANA LINCOLN COUNTY	
RECORDED: 12/14/2010 11:30 KOI: CCER'S	
FEE: \$0.00 BY: Season Season	
To: FILED , Cross Index NoC-13 _ T33N.R34WP.M., MT	

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

• corner this sheet