INSTRUCTIONS

 Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.

- Description of monument and accessories set to perpetuate the corner position.
 Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
 Fili in Cross Index & Seciton Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 1/4 sec. 2 & 35 T. 33 N R. 34 W P.M.M. Lincoln County

1. record: set a limestone 18x8x6 inches 12 inches in the ground for 1/4 sec. cor. marked 1/4 on west face from which:

> a Tam. 6" diam. bears S 70 E 2 lks. dist. marked 1/4 S2 BT

a Pine 5" diam. bearson 29a15" W37 Tks . dist.dist. marked 1/4 S35 BT

- 2. Found: found stone undisturbed with original Tam. BT. now 18" diam. scrib overgrown. a 20" Fir bears N 37 W 14.0 ft. dist. marked 1/4 S35 T34N R34W BT; set by M. D. L. in 1984
- 3. Accessories: set a 3x24 inch alum. monument stamped:

T34N R34W \$3<u>5___</u> S 2

T33N R34W

set a 6' steel post approx. 3' from monument maintained bearing trees with paint and sign's.

