Described frequencies of to evaluate the corner resitten

3. Description of monominal and accessories set to perpendice the corper position

4. Shorth or corner, show all perform data which can best be shown in a sketch example, corner marking, topography fles, position of accessories, etc.

Certification must be signed and sealed by Registered Land Surveyor in State of Montans.

CERTIFIED CORNER RECORDATION

W 1/16 S 21 T. 33N R. 3'M P.M.M. Lincoln Corner

RECORD: The original G.L.O. survey was conducted by Allen B. in 1905.

The monument was set during Exchange Survey No. conducted by Donald Sawhill in 1942..... 1258 as

Set an iron post, 3 feet long and 2 inches in diameter, inches in the ground, with broken glass deposited at the base, with brass cap stamped "17 ES 1258 CW 1/16 821 1941",

A cross on an 8" white fir bears N57 50'W, feet), marked "1/16S 17 ES 1250 BT". 45 links (29.70

A cross on a 10" douglas fir bears N41 45'E, 35 links feet), marked "1/16S 17 ES 1258 BT".

FOUND: Found the brass cap and iron pipe flush with the ground marked as shown below. No evidence of original BT's found.

MAINTENANCE: Established 2 new bearing trees.

400

A 71/2" cedar bears N69 W, 18,9 feet, marked "CW 1/16 S21 BT" A 6" hemlock bears N18 W, 65.8 feet, marked "CW 1/16 S21 BT" The blazes were painted red and a 6" band was painted around each bearing tree.

Bearing tree tags were attached to the front of each bearing tree. A Land Monument sign was nailed to the back of the codar bearing tree and an Attention sign was nailed to the back of the hemlock bearing tree.



CW SKETCH OF CORNER

CERTIFICATION Steven R. Moyer certify the information shown herein is true and correct. Signature Ground Party Chief Carl R. McMillen certify that this Corner Record correctly represents work performed Date 4-10-89 1. No. 46598

Employer: Tri-State Land Surveying

Lincoln Office of Clerk and Recorder, County of _ ___. This "corner _ day of 19*89* was noted on the cross-index plat and is assigned page No. 4056 book No.

Sec. 21

* - corner this shoot

Cross trace to P-10 +33N n 3'W trace