INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated.

III. At the position determined by survey; set an aluminum rod, 3/4 ins. diam., 30 ins. long, 29 ins. in the ground, with 3 1/4 ins. diam., U.S.D.A. Forest Service aluminum cap, marked as shown:

- 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

_ T. ____33 N., R. ___34 W., P.M.M. C-W-W-W 1/256 S21 Lincoln Corner_ _County No records found. II. No evidence found on the ground.

> \$21 C-W-W-W х 1/256 7322LS

Established two new bearing trees:

A fir, 9 ins. diam., bears N4 $^{\circ}$ E, 8.7 ft. dist., mkd. C W W W 1/256 S21 BT. A fir, 6 ins. diam., bears S61 E, 39.7 ft. dist., mkd. C W W W 1/256 S21 BT.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

1992

Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, South, 3 ft.

Magnetic Declination: 20 East

			· · · · · · · · · · · · · · · · · · ·	
		•	CER	TIFICATION
	A		, Thomas M. Ho	mmel
Λ	↑ ~"	FIR	certify the information shown	herein is true and corp.
4	, A 5	<i>,,,</i> ,	1	nt I
l,	44/1.		Signature (Ground Party Chief
~	47,1 81		, Alvah F. Hug	hes
	o 8 · ·		certify that this Corner Record	correctly represents work parformed
			by me or under my directi Recordation, Act'' (70-22-101, a	on in compliance with the Colrect
			Recordant April 100	7 No ALVATOR
	<i>چ</i> و	` ``````	Signature	of Support Control
	_	- A.J.	12/28/92	732228 32211 813
		· 🔪 🐧	Date:Reg. No	AC . 907 2 107 apr 17 1
	SKETCH OF CORNER	6" FIR	Employer: U.S. FORE	ST SERVICE
		1 ' 0	· · · · · · · · · · · · · · · · · · ·	Sec. 21 (1)
Office of Clerk and R	decorder, County of	uniot	. This "corner	
311 613 3.6		In 19 190	7.2	- 1
record" was filed for	record on	<u> </u>		
		mad nama Na	5299 in	
was noted on the cros	ss-index plat and is assig	gned page No.		
hools No	/ 1	alM. Gis	nmin RIB	
book No.		County O		

_ T. ____ R. ___ 34 W

· - corner this sheet