## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

ORIGINAL G.L.O. NOTES: CORNER NEVER SET

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

This corner was set from the section breakdown as indicated on the back. Set 24" X 30" Aluminum monument with 34" cap. Marked as shown.

18" Fir scribed
CN 1/16 BT

Cor. Mon.

201
14" Larch scribed
CN 1/16 BT

Date of work: MAY 1980

REST SEPLICE

N //6 SII

STANGES 2300

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE BACK

		DIAGRAM OF CORNER:
Surveyor's Seal	I, JAMES BURTON  certify that the information shown herein is true and correct.  Signature of Ground Party Chief  I, M. L. HAIGES  certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same  Signature of Surveyor  2520S  Registration Number	CN 1/16 SEC. 11  = Corner recorded on the sheet
Office of Clerk and Record This "corner record" was assigned page No.	filed for record on the 17th day of July 1980, was	s noted on the cross-index plat and is  August Sty Detty December 1981

## SECTION // BREAKDOWN AND H.E.S. 1238

