CERTIFIED LAND CORNER RECORDATION

WEST BOUNDART OF SECTION 17 TWP. 33 N., R. 34 W., P.M.M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Corner not established on ground previously

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 9/9/180

1.72

W 1/4 W 1/4 of Section 1(-mp.)

Idaho| S 17
Set 5/8"x24" Steel Rod with Yellow Cap stamped: J.H.N. 4661 S
8" Fir bears N 31°33' E 41.8 feet) Both posted &

---- S 14°40'E 14.1 feet) Scribed: W 1/4 B.T. W 1/4 of Section 17 Twp. 33 N., R. 34 W., P.M.M

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

TWP. 61 N., R. 3 E., P.M. 1. /DAHO 4372.50')-4372.50') 4362.09' (NORTH 34.25 d. 2266 NORTH >> -0°02'50"E **7** ₩ MONTANA DIAGRAM OF CORNER:

Surveyor's Seal

David Stanley certify that the information shown herein is true and correct. Signature of Ground Party Chief

Jack H. Ninneman certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor 1661 O = Corner recorded on the sheet

4661 S. Registration Number

Office of Clerk and Recorder, County of

This "corner record" was filed for record on the 2nd day of Alcember, 1980, was noted on the cross-index plat and is

assigned page No. 9.3/...., in book No. ...

Cross Index No. D-L T 33N R 34 W

w 1/4

IDAHO 1 S 17

... Мег.

8" FIR

3 Form 125—7887