## CERTIFIED CORNER RECORDATION

Corner C-E-E 1/64th Cor Sec 7 T. 34N R. 25W P.M.M. Lincoln County

- 1. NONE
- 2. NONE
- 3. Set:


An Aluminum Cap, 3½ ins. diam., on 5/8 ins. Rebar, set 0.4 ft. above ground, mkd. as shown; Established:

A Douglas Fir, 15 ins. in diam., bears N8°E, 35.1 ft. dist., scribed "C-E-E 1/64 S7 BT"; A Larch, 13 ins. in diam., bears N51°E, 53.2 ft. dist., scribed "C-E-E 1/64 S7 BT"; Steel posts with decals bear East and South, 2.0 ft. dist.



## MAGNETIC DECLINATION - 15"2' EAST

15" D Fir N8E, 35.1' 31 Larch N51E, 53.2' Steel Posts East & South, 2.0'



## SKETCH OF CORNER

Office of Clerk and Recorder—County of Lincoln 230078 BOOK: CCR CCCR'S ....This. "corner PAGE: 11677 Pages: 1 record" was filed for recor. STATE OF MONTANA LINCOLN COUNTY RECORDED: 12/09/2010 10:37 KOI: CCER'S Was noted on the cross-if tammy D. Lauer Clerk and recorder By FEE: \$0.00 Dean book No. \_ P.O. BOX 1863, SANDPOINT, ID. TO: GLANE & ASSOC., INC. G-4 <u>G-5 t 34N R 25W</u> Cross Index No.\_\_

Sec. 7

corner this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

• . . .