CERTIFIED CORNER RECORDATION								
Corner _	SE 1/16th S	Sec 6	T. <u>34N</u>	. R	25W	. P.M.M	Lincoln	County
1. <u>NONE</u>								
	ebar with yellow p nted white set 1							
mkd. as s Established: A Larch, A Larch,		ears N56°E, bears N64°W,	12.00° ft. dist 8.30 ft. dist.	., scribed ., "SE 1/1	"SE 1/16	S6 BT";	Rebar, set (	0.2 ft. above ground,
								SOR STANK SEAL OF SEAL
MAGNETIC	DECLINATION -	- 15°2' EAS	:T				(	S · 6  LS 9748 2010 2010 2010
12" Lo N64"W		N56 Steel Pos	arch E, 12.0' :ts East, 2.0'			LAWRENG certify that the performed by the "Corner R		CATION  CATION
	H OF CORNER		Linco		. This "co		AHE & ASSOCI	
record" was	s filed for record/ on the cross-ind	23008: STATE OF 1 RECORDED: TAMMY D. 1 FEE: \$0.0 TO: GLANE &	9 BOOK: CCR MONTANA LINC 12/09/2010 LAUER CLERK	CCER'S OLN COUN 10:48 K AND REC	PAGE TY OI: CCER ORDER	: 11688 P	Legaly 83860,	Sec. 6

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

corner this sheet

And the second of the second o the contraction with the first of the contraction o AND THE RESERVE OF THE PROPERTY OF THE PROPERT The state of the s