CERTIFIED CORNER RECORDATION

Corner C-E-W 1/64th Sec 6 T. 34N R. 25W P.M.M. Lincoln County

- 1. NONE
- 2. NONE
- 3. Set:
 A Aluminum Cap, 3½ ins. in diam., on 5/8 ins. diam. rebar 0.4 ft. above ground, mkd. as shown;

Established:

A Douglas Fir, 9 ins. in diam., bears N42°E, 26.5 ft. dist., scribed "C-E-W 1/64 S6 BT"; A Douglas Fir, 8 ins. in diam., bears N78°E, 52.7 ft. dist., scribed "C-E-W 1/64 S6 BT"; Steel posts with LSM decals bear North and East, 2.0 ft. dist.



MAGNETIC DECLINATION - 15'2' EAST




9" D Fir N42E, 26.5'



8" D Fir N78E, 52.7

Steel Posts North & East, 2.0'



SKETCH OF CORNER

Office of Clerk and Records	rCounty. of	Lincoln .	This_"corner	- <u>-</u>
record" was filed for recore		CCR CCER'S		Pages: 1 '
was noted on the cross—ir	RECORDED: 12/09/ TAMMY D. LAUER			• • •
book No.	FEE: \$0.00 TO: GLANE & ASSOC.	BY P.O. BOX 1	B63. SANDPOINT.	D. 83860
	·	C-2 ex No.		
Adopted July 1, 1981,	Montana Board of Pi	rofessional Engineer	s & Land Survey	ors

-

corner this sheet

Sec. 6

Bidi englis alayar CHIII. Burner Constant Control of the Contr

ALTERNATION OF A STANDARD AND A STAN

And the state of the second of

Line of the second of the seco