CERTIFIED CORNER RECORDATION										
	Corner	MC Sec 5/ East Shor		. <u>34N</u>	R	25W	. P.M.M	Lincoln	_County	
1.	S5 on N. R25 From Which:	ginal Record by long, 4 ins. sqi bW on E. and S ins. in diam. be	uare, 24 ins 8 on South	i. in the grou faces.					Marked M.C.	on W. T34N
2.	A Spruce, 6 i	ns. in diam. be	ars S5975'E	, 131 lks. dist	t. marked	1 T34N R2	25W S8 MC	BT.	.i.	
_	The remains of Corner position	mp, 10 ins. in of a Spruce stu of a Spruce stu on falls in one	ımp, 12 ins.	in diam. N72			nt blaze, sc	PIDE NOT VISID	ole.	
	mkd. as show Established:	Cop, 3½ ins. on; along Section L				swampy (ground, set	1.0 ft. above	ground,	
									ř.	
								1	SOF JANR25	'A VICE
								(S8 LS 9740 2010 ASTRAL S	-MC B
	MAGNETIC DE	CLINATION -	15'2' EAST				-		· inne	
		м с С	N88'46'11" 116.8'	E⊕ wc			LAWRENC certify the state LAWRENC certify that the performed by the "Comp Re		ATION A A CONTROL OF THE CONTROL OF	
	SKETCH	OF CORNER					Date! Zirl	9748 Springerisi WAHE & ASSESSE	ES 9748	LS
	Office of Clerk	and Recorder,	230105 STATE OF N RECORDED: TAMMY D. I FEE: \$0.0	D BOOK: CCR MONTANA LINC 12/09/2010 MAUER CLERK MO BY	CCER'S	PAG NTY KOI: CCSI CORDER	E: 11708 R'S	Should	Sec. 5	
	Adopted	July 1, 1981, M	Cros	s Index No	E-7 E-8	т. <u>34N</u>	R. 25W Surveyors			

corner this sheet

,*,