

CERTIFIED CORNER RECORDATION

Corner E 1/16 S6 T 34 N. R. 25 W. P.M.M. Lincoln County

- I. Record: 2001 Certificate Survey No. 3063 Lincoln County Records, by D. Marquardt, 7328S.  
2005 Certificate Survey No. 3499RB Lincoln County Records, by A. Belski, 14731LS.
- II. Found: A field search found no monuments.
- III. Perpetuation: At the corner point, determined by survey, set a 5/8 ins. diam.  
steel rebar 24 ins. long, 22 ins. in the ground, with a 3 1/4 ins. diam.  
Aluminum cap marked as shown below from which:

A Douglas fir, 12 ins. diam., bears N29°W, 8.70 ft. dist., scribed E 1/16 S6 BT.

A Douglas fir, 6 ins. diam., bears S70°W, 14.40 ft. dist., scribed E 1/16 S7 BT.

Painted faces and 6 in. wide red bands to all bearing trees and attached Land  
Survey Monument and Bearing Tree signs.


Magnetic declination: 18° East

Equipment used: Hand compass and loggers tape



Kootenai Surveyors Inc., 314 California Av., Libby, MT. 59923 (406) 293-4354

NELSON Sec. 6



SKETCH OF CORNER

CERTIFICATION

I, Kelly Rooney  
certify the information shown herein is true and correct.

Kelly Rooney  
Signature Ground-Party Chief

I, Alvah F. Hughes  
certify that this Corner Record correctly represents work  
performed by me or under my direction in compliance with  
the "Corner Recordation Act" (70-22-101 et seq. M.C.A.)

Alvah F. Hughes  
Signature of Surveyor & Seal

Date: 4/8/2011 Reg. No. 7322LS

Employer: Kootenai Surveyors Inc.

Office of Clerk and Recorder, County of Lincoln This "corner

record" was filed for record 232230 BOOK: CCR CC&R'S PAGE: 11868 Pages: 1

was noted on the cross-STATE OF MONTANA LINCOLN COUNTY

book No. TAMMY D. LAUER CLERK AND RECORDER


FEE: \$0.00

TO: FILED

Cross Index No. E 04 T. 34N R. 25W P.M., MT

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

Sec. 6



• corner this sheet

100-443687-100