

INSTRUCTIONS


1. Original and subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

**CERTIFIED CORNER RECORDATION**

Corner Sec. Cor. Sections 17, 18, 19 and 20 T. 34N R. 25W P.M.M. Lincoln County

Original Record: Set a post 4' long x 4" square 24 ins. in the ground from which:  
 a tamarack 20" diam. bears N. 15° E. 25 lks.  
 a tamarack 20" diam. bears S. 37° 45' E. 10 lks.  
 a tamarack 23" diam. bears S. 62° W. 69 lks.  
 a fir 8" diam. bears N. 57° W. 28 lks.

Set aluminum cap from Ninneman RMs.



SKETCH OF CORNER

CERTIFICATION

I certify that the information shown hereon is true and correct.

Signature of Registered Land Surveyor

D.K. Marquardt  
 I certify that this Corner Record correctly represents work done by me or under my direction in compliance with the Recordation Act (70-22-101, et seq., M.C.A.)

D.K. Marquardt  
 Signature of Registered Land Surveyor

Date 7-9-81 Reg. No. 2989ES


Employer \_\_\_\_\_

Office of Clerk and Recorder, County of Lincoln This "corner record" was filed for record on the February 17<sup>th</sup> day of 1981 was noted on the cross-index plat and is assigned page No. 1532, in book No. 1

Eleanor L. Vaughn by Betty L. Conner  
 County Official deputy

Cross Index No. N-5 T. 34N R. 25W P.M.M.

Sec. 17



• corner this sheet

34 . 0072 . 01



*Handwritten signature or initials*