	1	* 71	<b>.</b>	<del>ت</del> ې					• •			
			INSTRUCTIONS  1. Original and/or symbol quent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or observances. 3. Description of monument and accessories set to perpetuale the corner position. 4. Saetch or corner, show all pertinent data which can best be shown in a sketch example, corner a topography lies, position of accessories, etc. 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana. 6. Fill in Cross Index & Section Diagram at bottom of sheet.						rner marking,			
			CERTI	FIED C	ORNE	R RE	CORDA	TION		, i e e e e La e e e e	e e e e e e e e e e e e e e e e e e e	
r NW	NW	1/64	Sec. 25	Τ.	34N.	. R	25W.	P.M.M.	LINCOLN		County	
	•							• ,,	sit is a	ه دي		
RECO	RD:	NO P	REVIOUS RECORD O	F CORNE	R ON FI	LE						
FOUN	D: N	IOTHI	NG TO SHOW EVIDE	NCE OF	A MONUM	ENTED	CORNER					
SET:	SET	A 3	1/2 " dia. ALUM	IINUM CA	P ONTO	A 4' I	bv 1/2" I	DIA. PI	PE. APPRO	X. 40"	in 😘 🥕	
			LOCATED IN BACK						•	•		
	•		AS APPROX. 4" DE				, .	:	•		• • •	
					THE CHP	MMS.	JEI CAP	,; ';	KUUNDED E	T A MUUI	10 OF - 1 - 14 - 77	
	210	INES .	AND MARKED AS SH	OWN:	5.5.	•	,	•		. , , , ,	ish i	
FROM	WHI	CH: I	A 3" DIA. ASPEN	BEARS N	19 W 2	7.4' :	SCRIBED	"BT" ,		a the star	2000	
f	•	i	A 7" DIA. PINE B	EARS S	23 E 52	.9' S	CRIBED 1,	/64 BT。	1.1.1.13 <u>.3</u> 16.1	1	· · · · · · · · · · · · · · · · · · ·	
		(	BT"S ARE PAINTED	RED.				, ,	•	الم خواليد،	ng Meri N	
						9.50	(a) B	# 1 1 7	of the suprem			
•		į		34 H	<b>R</b> .S			** *** · ·	erira i		e di Carabinan	
	•		. /	^		2.7		(m)				
			- 1	N	MNW		1.			•	, ,	

Corner.







