

- INSTRUCTIONS**
1. Original and subsequent record used to evaluate the corner position.
  2. Description of evidence found, make discrepancies in the record, state method of establishing lots or otherwise corners.
  3. Description of monument and accessories set to perpetuate the corner position.
  4. Sketch or survey, show all pertinent data which can best be shown in a sketch example, corner marking, topography, etc., position of accessories, etc.
  5. Certificate must be signed and sealed by Registered Land Surveyor in State of Montana.
  6. Fill in Cross Index & Deeding Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner 1/4 30 29

T. 34N

R. 25W

P.M.M. Lincoln

RECORD: Original G.L.O. - 1894


County

B.L.M. remonumentation notes.

The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, as determined from the remains of the original bearing trees.

At the corner point

Set an iron post, 30" long,  $2\frac{1}{2}$ " diam., 26" in the ground, in concrete, with brass cap mkd.



from which

The remains of the original bearing trees:

A stump, 15" diam., bears N.33 E., 17 lks dist., mkd. with overgrown blaze. (RECORD)

A stump, 13" diam., bears S.52 $\frac{1}{2}$  W., 20 lks. dist., mkd. with overgrown blaze. (RECORD)

The new bearing trees:

A fir, 8" diam., bears S.40 $\frac{1}{2}$  E., 39 lks. dist., mkd.  $\frac{1}{4}$  S29 BT.

A fir, 6" diam., bears S.55 $\frac{1}{2}$  W., 64 lks. dist., mkd.  $\frac{1}{4}$  S30 BT.


Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the iron post.

FOUND: A  $4\frac{1}{2}$ " diam. B.L.M. brass cap approx. 1 ft. above ground adjacent to mound of stone, mkd. as shown above.

from which

A fir 10" diam., bears S.39 E 26.1 feet dist., healed face.

A fir 9" diam., bears S. 57 W. 41.5 feet dist., healed face.



CERTIFICATION

James W. Reed

I certify the information shown herein is true and correct.

James W. Reed  
Signature of Surveyor & Seal

Thomas C. Hill

I certify that this corner record correctly represents work performed by me or under my direction in compliance with the "Surveyor Registration Act" 18-38-105, M.R. 4-1.

Thomas C. Hill  
Signature of Surveyor & Seal

Date: 3/15/83 Reg. No. 5612 S


Employer: U.S.F.S.



**SKETCH OF CORNER**

Office of Clerk and Recorder, County of Lincoln  
record" was filed for record on the June 16 day of 1883  
was noted on the cross-index plat and is assigned page No. 2235, in  
book No. Janet & Siegel by Betty L. Concas  
County Official deputy

Sec. 29



Cross Index No. T-5 T. 34 R. 25 P.M.M.

\* corner this sheet

100-1000

100-1000  
100-1000

100-1000

100-1000 100-1000

100-1000  
100-1000