DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No Original Record.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

> 1979 Date of work:..

Set a 3 x30" aluminum pipe approx. 24" in ground with alum. cap marked:

Form a stone collar. From which:

A 13" fir bears N89°11'W 44.1ft., scribed N1/16 S24BT.

A 15" spruce bears N14°48'E 32.6ft., scribed N1/16 S19BT.

Place N.F. Property Boundary post and ATTENTION sign at corner position.

T34N N:1 7<sub>16</sub> R26W R25W S24 **S19** 5612S 1979

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. 749

ONTA HOMÁS C. HILL 5612 S SURVE THE

Surveyor's Seal

certify that the information shown herein is true and correct.

Signature of Ground Party Chief

Thomas C. Hill certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

> مرس Signature of Surveyor

DIAGRAM OF CORNER:

T34N N. N 1/16 Sec . 24 Sec. 19 **R26W** R25W

= Corner recorded on the sheet

561.28

	Registration Number
Office of Clerk and Recorder, County of Lincoln	
	March 19.80, was noted on the cross-index plat and is
assigned page No. 28/ in book No	Eleanor L. Vaushn by Sherry L. Bawks County Official Digente Cross Index No. D25 T. 34 R. 25 Mer.
	Cross Index No. 025 T. 34 R. 25 Mer.

And the second of the second o total services and and Note: See the profit of the seed of the see I Commence to the first of the second of the

The state of the s