

INSTRUCTIONS

1. Original and/or recent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner South 1/4 Section 32 T. 34N R. 26W P.M.M. Lincoln County
1/4 To Section 32 only

GLO Record: Set post 3' long 3" square 24" in the ground for
 1/4 section corner marked "1/4 S" on North face,
 from which:

10" Spruce mkd. "1/4 S BT" bears N55°30'W 26 lks.

10" Pine mkd. "1/4 S BT" bears S71°45'W 37 lks.


Found: Partially rotted remains of original post in ground.
 A 3" x 4' long post lies 2' north of this location;
 however, this post does not appear to be part of
 the original.

Base of original bearing tree bears S71°W 23.8';
 the trunk of the tree is lying on its side with the
 blaze facing away from the corner. "1/4 S BT" is clearly
 scribed on the blaze.

New Monumentation: At the point marked by the location of the
 base of the original post, I set a standard 2" diameter
 aluminum monument with 3" cap, marked and witnessed as
 described below. No stones for mound available.

8" Cedar scribed "1/4 S 32 BT" bears N74°E 29.28'

7" Tamarack scribed "1/4 S 32 BT" bears N12°W 4.78'



SKETCH OF CORNER

CERTIFICATION

I, _____
 certify the information shown herein is true and correct.

Signature Ground Party Chief

I, S. R. Smith
 certify that this Corner Record correctly represents work performed
 by me or under my direction in compliance with the "Corner
 Recordation Act" (70-22-101, et seq., M.D.A.)

Signature of Surveyor & Seal

Date: 11/19/82 Reg. No. 47405


Employer: Smith Surveying Co.

Office of Clerk and Recorder, County of Lincoln. This "corner
 record" was filed for record on the July 28th day of 1982
 was noted on the cross-index plat and is assigned page No. 1832, in
 book No. _____

Eleanor L. Vaughn by Betty L. Conner
 County Official deputy

Cross Index No. 2-7 T. 34N R. 26W P.M.M.

Sec. 32



• - corner this sheet

1/4 To Section 32 only

