INSTRUCTIONS

1. Original and/or aubsc record used to evaluate the corner posttlen.

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

3. Description of monument and accessories set to perpetuate the corner position.

4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ites, position of accessories, etc.

5. Certification must be signed and sealed by Registered Land Surveyor in State of Montans.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

N1/16 27/26 T. 34N R. 26W P.M.M. Lincoln

Record of Original Corner No previous record on file.

<u>Description</u> of <u>Corner</u> <u>Evidence</u> <u>Found</u> No evidence found on ground


## Description of Monument and Accessories Set

Set a standard 3 1/4" dia. Forest Service aluminum cap on a 3/4" x 30" aluminum shaft 24" in the ground with a rock cairn from which:

An 11 1/2" larch bears N70°E, 11.5 ft. dis. scribed N1/16S26BT

A 6" larch bears S23°W, 27.4 ft. dis. scribed X BT

Bearing trees were signed and blazes painted red. Placed a 6 ft. steel post with Land Survey Monument decal attached 6 ft. west of corner. Corner falls at top of steep east slope in open timber. Placed a K tag on a 7 1/2" lodgepole pine on south side of road 64' north of corner.



	STAPLES 9958 LS  PEGISTERED OF THE PERIOD OF
N 70°E  1/5  SKETCH OF CORNER	CERTIFICATION  1. Steven R. Mover  certify the information shown herein is true and correct.  Signature Ground Party Chief  1. James R. Staples  certify that this Corner Record correctly represents work performed by the or under by direction in compliance with the "Curner Recordation Act" (70 22-101, et seq., M.D.A.)  Signature of Surveyor & Stat  Date: 10/5/90 Reg. No. 9958LS  Employer: J.R.S. & Associates
Office of Clerk and Recorder, County of	Sec. 27  This "corner day of 1986  Sec. 27

