INSTRUCTIONS

I record used to evaluate the corner position.

2. Description of evidence found, note discrepancies in the record, state method of establishing loss or obliterated

3. Description of monument and accessories set to perpetuate the corner position.

4. Shotch or corner, show all pertinent data which can best be shown in a sheich example, corner marking, topography ites, position of accessories, etc.

2. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Lincoln 26W CN1/16 S32 P.M.M., Corner _ County

Record of Original Corner No previous record on file.


Description of Corner Evidence Found No evidence found on ground

Description of Monument Set

Set a standard 3 1/4" dia. Forest Service aluminum cap on a 3/4" x 30" aluminum shaft 25" in the ground from which:

A 13" larch bears $$66^{\circ}E$, 17.5 ft, scribed CN1/16S32BT A 14" cedar bears $$36^{\circ}W$, 18.6 ft, scribed CN1/16S32BT

Bearing trees were signed and blazes painted red. Placed 6 ft. steel post with Land Survey Monument decal attached 6 ft. east of corner. Corner falls in cedar thicket on moderate east slope.



	9958 LS 9958 LS 9958 LS 9958 LS 9958 LS
SKETCH OF CORNER	CERTIFICATION 1. Steven R. Moyer certif, the information shown herein is true and correct. Signature Ground PartyChief 1. James R. Staples certify that this Corner Record correctly represents work performed by the or under by direction in compliance with the "Curner Recordation Act" (7021-101, et seq., M.D.A.) Signature of Surveyor & Seal Date: 10/5/90 Reg. No. 9958LS Employer: J.R.S. & Associates
Office of Clerk and Recorder, County of	Sec. 32 - This "corner day of 1990 330 In Ly Bul Bull clai - Corner this sheet

H STANKS IN COLOR