CERTIFIED LAND CORNER RECORDATION --

DESCRIPTION OF COR	NER EVIDENCE FO	OUND, AND ORIGINAL	RECORD (IF KNOWN)
--------------------	-----------------	--------------------	-------------------

QUIGINAL G.L.O. NOTES: "S. shore of Mud Lake- The sec. cor. falling in the lake cannot be established so i establish a W.Cor as follows Set a post 4ft. long 4 ins. square 24 ins. in the ground for W. Cor to cor to secs 3,4,9 & 10 marked W.C. and with T34N S3 on N.E. R26W. S 10 on S.E. S 9 on S.W. and S 4 on N.W. faces with 5 notches on S & 4 notches on E. edges from which A spruce 8 ins. diam. bears S.6045'E 128 1ks.

dist. marked T.34N. R26W S.10 W.C.B.T.

A spruce 8 ins. diam. bears N.51°30'W 27 lks. dist. marked T.34N.

R26W S.9 W.C.B.T."

FOUND:

FOUND S.E. BEARING TREE AND ORIGINAL POST

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

ORIGINAL EVIDENCE FOUND

NEW EVIDENCE SET

8" Spruce scribed "WC S9 RM"

Original post

10" Spruce

o 1" X 30" Alu. mon. with 3½" cap marked as shown.

Date of work:

Aug. 1979

LAND

LAND

WC

4 13

9 10

Rep. 1865

2520 5

scribing visible

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal

JAMES BURTON

certify that the information shown herein is true and

Signature of Ground Party Chief

M. L. HAIGES

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

= Corner recorded on the sheet

DIAGRAM OF CORNER:

SOUTH WITNESS

COR. TO SECS. 3,4,9 § 10

T34N

Registration Number

Office of Clerk and Recorder, County of Sincala)

This "corner record" was filed for record on the Alate. day of Afficient 1979, was noted on the cross-index plat and is sanigned page No. 55/, in book No.

Eleman J. Danaha, hey betty ball County Official Separty

Form 125-45227

Cross Index No. E. 13, T. 34, R. 26, Mer.

- J . . . ·· **'.** · . .