
CERTIFIED CORNER RECORDATION

Corner CW 1/16 Sec. 7 T. 34N R. 26W P.M., MT Lincoln County

- I. No previous history.
- II. Nothing found.
- III. At the position as determined by survey, set a 3/4 ins. diam., 30 ins. long alum. rod, with a 3 1/4 ins. diam. alum. cap, 7 ins. above ground, marked as shown:



Established two bearing trees:

A larch, 9 ins. diam., bears S20°W , 31.7 ft. dist., scribed "CW1/16 S7 BT". A fir, 15 ins. diam., bears N71°W, 29.9 ft. dist., scribed "CW1/16 S7 BT".

Painted bearing trees and attached Land Survey Monument and Bearing Tree signs.

Set a 6 ft. galvanized steel post, North, 3.0 ft. dist., with Land Survey Monument and Property Boundary decals.

Magnetic Declination: 20° East.

SKETCH OF CORNER	I. Alvah F. Hughes certify that this Corner Record correctly represents work performed by me of eoder my direction in compliance with the "Corner Recordation Act" (76-22-101) et sea; M.O.A.) Signature of Surveyor a Sea! Date: 12/11/96 Reg. No.: 7322LS Employer: U.S. FOREST SERVICE
Office of Clerk and Recorder, County ofLINCOLN This "corner record" was filed for record onFEB 3,1997 and was noted on the cross-index plat and is assigned page No.9/92 , in book No CORALM.CUMMINGS County Official	

Cross Index No.

G-02

⁷ 34N

^{R.} 26W

•

CERTIFICATION

