## CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1960	$B_{\bullet}L_{\bullet}M_{\bullet}$	record,	from	found	orig	ina	d ev.	ider	ice: S	et an	iron	post,	, 30 in	s. :	Long,
			2⅓ in	s. di:	am.	26	ins.	in	ground	with	brass	cap	marked	as	shown:

From which: A 18" larch bears N38°45 W., 32 lks. Scribing visible. A 9" fir bears S61°E., 110 lks. Marked: "4 S 34 BT."

Found a 2"  $B_{\bullet}L_{\bullet}M_{\bullet}$  pipe appr. 7" above ground with brass cap marked as shown: Mound of stone appr. 1.5 ft. N. of pipe.

From which: A 15" larch bears N32° E., 21.2 ft. Scribing visible, alive and well A 14" fir bears S59° E., 72.9 ft. Healed face, alive and well.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

8/12/80 Date of work:

Painted red bands around bearing trees.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



Anthony J. Bachman

certify that the information shown herein is true and

Signature of Ground Party Chief

Thomas C. Hill certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

5612-S

Registration Number

DIAGRAM OF CORNER: T34N R26W SEC 27 = Corner recorded on the sheet

Office of Clerk and Recorder, County of ... Q This "corner record" was filed for record on the

. . . . • . • - 1 1 4 . ::... · - :