CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1960 B.L.M. record, from found original evidence: Set an iron post with brass cap marked

as shown:

A pine snag bears $NO1\frac{1}{2}^{\circ}W_{\bullet}$, 31 lks. Marked: " $\frac{1}{4}$ S BT." A 10" fir bears $S66\frac{1}{2}^{\circ}E_{\bullet}$, 37 lks. Marked: " $\frac{1}{4}$ S3 BT." A 8" fir bears $N28\frac{1}{2}^{\circ}W_{\bullet}$, 54 lks. Marked: " $\frac{1}{4}$ S34 BT." From which:

534 53 733N 1960 BLM

Found a $2\frac{1}{2}$ iron pipe appr. 5" above ground with brass cap marked as shown: Collar of stone.

From which:

A 12" snag bears North, 21.0 ft. Scribing visible.

A 12" fir bears S65°E., 25.3 ft. Scribing visible, alive and well.

A 10" fir stump bears N28°W., 35.7 ft.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

8/25/80

Date of work:..

Painted red bands around bearing trees.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



I, Anthony J. Bachman certify that the information shown herein is true and

Signature of Ground Party Chief

Thomas C. Hill

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

5612-S Registration Number DIAGRAM OF CORNER:

N. 734N R26W

SEC 34

5EC 3

ナ 33人 = Corner recorded on the sheet

Office of Clerk and Recorder, County of.

This "corner record" was filed for record on the was noted on the cross-index plat and is

<u> 2-15</u>

. A 577 . \bigcirc