CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1960 B.L.M. record, from found original evidence: Set an iron post with brass cap marked

From which: A 7" fir bears N58° 45' E., 59 lks. Marked: " $\frac{1}{4}$ S29BT." A 7" fir bears Shh $\frac{1}{2}$ ° W., hh lks. Marked: " $\frac{1}{4}$ S32 BT."

Found a $2\frac{1}{2}$ pipe appr. 2" above ground with brass cap marked as shown:

From which: A 9" fir bears N59°E., 39.4 ft. Scribing visible, alive and well. An 11" fir bears S43°30W., 28.9 ft. Healed face, alive and well.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 8/13/80

Painted red bands around bearing trees.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



Anthony J. Bachman certify that the information shown herein is true and correct.

Signature of Ground Party Chief

Thomas C. Hill

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this

recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

T34N R26W

= Corner recorded on the sheet

5612**-**S Registration Number

Office of Clerk and Recorder, County of Lincoln	
	February 1981, was noted on the cross-index plat and is
assigned page No. 286, in book No	Eleanor L. Vaughn by Michele Groom
	Cross Index No. V-7 T 34N P 26W Year

•