CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53).

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1960 B.L.M. record, from found original evidence: Set an iron post, 30 ins. long,

 $2\frac{1}{2}$ ins. diam., 26 ins. in ground with brass cap marked as shown: From which: A 5" larch bears N15 $\frac{1}{4}$ °E., 18 lks. Marked: " $\frac{1}{4}$ S27 BT." A 5" larch bears S83 $\frac{1}{4}$ °W., 36 lks. Marked: " $\frac{1}{4}$ S28 BT."

Found a B.L.M. pipe appr. 3" above ground with brass cap marked as shown: Mound of stone appr. 1.0 ft. West.

From which: A 10" larch bears Nlh°E., 12.2 ft. Healed face, alive and well.

A 9" larch bears S8h°W., 2h.0 ft. Healed face, alive and well.

528/527

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 8/12/80

DIAGRAM OF CORNER:

SEC 27

Painted red bands around bearing trees.

Surveyor's Seal

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

T34N R26W certify that the information shown herein is true and Signature of Ground Party Chief 5EC 28 I,Thomas C. Hill certify that I have carefully performed or reviewed the THOMAS C HILL work done on the diagrammed corner as reported on this recordation form, and approve the same. Corner recorded on the sheet SURVE Communication of the second of Signature of Surveyor

Anthony J. Bachman

5612-S Registration Number

This "corner record" was filed for record on the 4th day of February 19.81, was noted on the cross-index plat and is 988....., in book No....... Cross Index No. T-13 T 34 N

8 ()