CERTIFIED CORNER RECORDATION


27W P.M., MT County 34N Lincoln 1/4 1 & 12 Corner

1912 G.L.O. Original Record by William C. Perkins: Set a shale stone, 18x10x6 ins., 14 ins. in the I. ground, for 1/4 sec. cor., mkd. "1/4" on the N. face..

Established two bearing trees:

A larch, 12 ins. diam., bears N14°E, 39 lks. dist., mkd. "1/4 S1 BT". A fir, 6 ins. diam., bears S39°E, 24 lks. dist., mkd. "1/4 S12 BT".

1961 B.L.M. Remonumentation Record by David R. Cunningham et. al.: The 1/4 sec. cor. of secs. 1 & 12, monumented with a shale stone, 18x10x6 ins., firmly set and mkd. "1/4" on the N. face, and witnessed by the remains of the original bearing trees. At the corner point, set an iron post, 30 ins. long, 2 1/2 in. diam., 26 ins. in the ground, in concrete, with brass cap mkd. as shown.



Established two new bearing trees and bury the original stone alongside of the iron post.


Found a B.L.M. brass cap, firmly set, protruding 3 ins. above the ground, mkd. as shown above. II.

from which:

A larch, 17 ins. diam., bears N16°E, 25.1 ft. dist., with visible scribe. (GLO-record-N14°E) A dead fir, 6 ins. diam., bears S36°E, 18.5 ft. dist. (GLO-record-S39°E, 24 lks., 15.84 ft.) A spruce, 18 ins. diam., bears S50°E, 36.2 ft. dist., with a healed face. (BLM-record) A pine, 13 ins. diam., bears N14°W, 30.2 ft. dist., with a visible scribe. (BLM-record)

Painted bearing trees and attached Land Survey Monument and Bearing Tree signs. III.

Magnetic Declination: 20° East.



F-23

27W