## INSTRUCTIONS



1. 2. 3. 4. 5. 6. INSTRUCTIONS

Original and/or subsequent record used to evaluate the corner position.

Description of evidence found, not discrepancies in the record, state method of establishing lost or obliterated corners.

Description of monament and secessories set to perpetuate the corner position.

Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of secessories, etc. Certification must be signed and sealed by Land Surveyor registered in the State of Montans.

Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

			CERTI		OKTATA	17 1717	CONDAI	1011	
Corner_	CE1/16	Sec.	13 T	. 34N	R	27W	P.M.M	Lincoln	County
Said sul	bdivisio	nal sur	vey was m	ade in acc	cordance	e with	a subdivis methods and d Managemen	d procedure:	ey of the section. s contained in the
FOUND:	No evid	ence f	· ound.						
<u>PERPETU</u> reverse from wh	side:	Set a	3/4"x30"	aluminum	rod wi	ith 3¼'	'aluminum	cap marked	l as shown on the
							1/16 S13 B1 1/16 S13 B1		
Bearing Monumen	tree ta	ags we: were p	re placed laced on	on the	•		•		and Land Surve
<u></u>							· ·-	CERTIFICATI	
	SEE	REVERS	SE SIDE FO	DR DIAGRAM	1		Signature Foundation I. James R. State certify that this corner R	hown, herein is true and o	work promod IAMES P
							Signature of Sur	veyor & Seal	9958 LS
							Date: <u><b>7-20 - 9</b>8</u> R	eg. No. 9958	SURV
		SKET	CH OF COR	NER			Employer: J.R.S. St		Sec. 13
Office	of Clerk	and R	ecorder,	County of	Line	L	· This "		Sec. 13
			record o	(/	m	rih	3,1997	9	
			s-index p		s assig	ned pa	ge No 103	13 <sub>n</sub>	
book No				Con	al M	1. lin	mmin b	Pels	
						count	y Official/		
,									

Cross Index No. <u>L24</u> T. <u>34N</u> R. <u>27W</u> PMM

34N 72/2 6712 C = 1/8 C 732215 1998

Salah Sa



ij