## CERTIFIED LAND CORNER RECORDATION

Cor. 14,13,23,24, Twp. 34N, R29W

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) Original 1912 GLO Notes, Vol. 6501, page 7&8, T34N,R29W, Lincoln County, Montana Cor. Desc. Slatestone 18"x12"x5", 12 in grd, Mkd W/3 Notches on S and l Notche on E. edge Witness Marks, 12" Pine bears N50, 1.12 chs, Mkd. T34N, R29W, S14 BT 8" Pine bears N78°E, 61 lks, Mkd. T34N, R29W, S13 BT, 26" Pine bears S570W,48 lks, Mkd. T34N,R29W,S23 BT, 30" Pine bears S 310E, 70 lks Mkd. T34N,R29W,S24 BT
Found: August 1966 Original stone firmly in place marked as reported. All four bearing trees alive and healthy-all partly legible, partly overgrown, all four positive identification.

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

25/8/66 Date of work:

We set a Std. monument with Brass Cap marked T34NR29W

Set original stone alongside-in mound of stone, Tagged all four BTs with Standard FS BT signs.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

## – See other side $\sim$

Surveyor's Seal	Jack Ninneman	DIAGRAM OF CORNER:
	certify that the information shown herein is true and correct.  Signature of Ground Party Chief	N.
	Jack Ninneman	23 24
	I,certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	T.34N, R.29W.
	Signature of Surveyor	= Corner recorded on the sheet
	Montana 534 ES	
	Registration Number	

This "corner record" was filed for record on the 5th day of January 19.67, was noted on the cross-index plat and is

assigned page No....67 in book No....1

FORM 125 - 41483

VAUGHN, By

Cross Index No. N-21' T. 34 R. 29 Mer.

By:

Deputy.

Re ported 12" Pine Mkd. T 34 N R 29 W S 14 B T

Now 28" Y. Pine Partly legible We tagged With Std. FS BT sign

> Reported 8" Pine Mkd. T 34 N R 29 W S 13 BT Now 16" Y. Pine Partly legible We tagged with std. BT sign.

We set std. brass capped mon. marked thus in mound of stone 23 24 1966 N 18°E

14

)N STEEP WEST SLO PE

Reported 26" Pine Mkd. T 34 N R 29 W S 23 BT Now 32" Y. Pine Partly legible We tagged with std. FS BT sign. T. 34 N., R. 29 W.

Minder BARE ROCK 20 FROM SE DAZE Reported 30" pine Mkd. T 34 N R 29 W S 24 BT Max. 20 High Long SE William Broken 20 High Back 20 High

Max. 20 HIGH