

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

1 of HES 1064 34 N. 32 W. Lincoln
 Corner T. R. P.M.M. County

- I. 1921 H.E.S. original record by Grant Higgins: Set a limestone, 10 x 9 x 7 ins. above ground, mkd. 1HES1064, 2HES1072 and 4HES1242, with cross (x) on top for exact corner position.

from which:

- A cross (X) on a larch tree, 8 ins. diam., bears S. $26^{\circ} 24'$ W., 97 links dist.
 A cross (X) on a larch tree, 7 ins. diam., bears S. $80^{\circ} 40'$ W., 75 links dist.

Each blazed and scribed 1 H E S 1064 BT.

Raise a mound of earth 4 ft. base, 2 ft. high, NE. of corner.

- II. Found a limestone, 10x9x7 ins. above the ground, mkd. 1 HES 1064 on the N. face, 4 HES 1242 on the West face and 2 HES 1072 on the South face, firmly set with a 10 ft. diam. x 4 ft. high mound of machine placed rock West of corner.

No accessories found.


Corner position checked by survey.

- III. Established two bearing trees:

- A larch, 15 ins. diam., bears N. 10° E., 46.1 ft. dist., scribed 1 HES 1064 BT.
 A spruce, 10 ins. diam., bears N. 60° W., 21.6 ft. dist., scribed 1 HES 1064 BT.

Painted red bands around the bearing trees and attached "Land Survey Monument" and "Bearing Tree" signs where needed.

Magnetic declination: 20° East



SKETCH OF CORNER

CERTIFICATION

I, Kenneth Kern
 certify the information shown herein is true and correct.

Kenneth R Kern
 Signature Ground Party Chief

I, Alvah F. Hughes
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-10), et seq., M.C.A.

Alvah F. Hughes
 Signature of Surveyor & Seal

Date: 11/26/91 Reg. No. 7322-LS 7322-LS

Employer: U.S. FOREST SERVICE

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on 4-21-92 was noted on the cross-index plat and is assigned page No. 5031, in book No. Coral M. Cummings


County Official

1 HES 1064

34 N

32 W

Cross Index No. T. R. PMM



• - corner this sheet