## **CERTIFIED LAND CORNER RECORDATION**

(REFERENCE FSM 7153.53)

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original stone firmly set and plainly marked, pits and mound were found and very distinct. (Record - set a small stone, marked with a cross (x), under a shale stone 24 X 8 X 8 ins. 14 ins. in the ground marked 12 HES 740 on SW face and a cross (x) on top for exact corner point. No bearings available, therefore dig pits 24 X 24 X 12 ins.crosswise on this and the succeeding course 7 ft. distant, and raise a mound of earth 4 ft. base, 2 ft. high, SW of corner)

## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 12/4/69

I set a 2 inch galvanized iron pipe, 18 inches in ground, with brass cap marked, and raised a collar of stone, 2 ft. base 1 ft. high around the iron pipe. I set the iron pipe in the exact position of the original stone corner monument and buried the original stone alongside the iron pipe. From which:
a 8 inch Larch bears N  $74\frac{1}{2}^{0}$ W - 24 links, scribed 12 RM A 6 inch Larch bears S 65° E - 26 links, scribed 12 RM

18 HES 740 SJ 1969 S

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original field notes.)

Surveyor's Seal

I, A. R. Trenkle certify that the information shown herein is true and correct.

a. R. Tunble

Signature of Ground Party Chief

Stanley J. Skousen

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

2532 S

Registration Number

DIAGRAM OF CORNER:

T34N R33W

13 HFS 740

N.

= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "sorrer record" was filed for record on the 19th. . . . . February to 70

This "corner record" was filed for record on the 19th. day of February 1970, was noted on the cross-index plat and is assigned page No. 170, in book No. 1 ELEANOR L. VAUGHN, By: The Walson

County Official Deputy.

Cross Index No. V-23 T. 34 R. 38 Mer