			CERTIFIE	D CORN	ER REC	ORDAT	ION	
Со	rner	WE 1/64	33	T34_N	R <u>3</u> 4	<u>4 W. </u>	P.M.M. <u>Llì</u>	NCOLN County
I.	1981 Ce	rtified Corne	r Recordation by X30" alum, pipe	Thomas C.	Hill, MT Reg	<u>, No. 5612</u> I. collar of	S: At the	determined corner lum. cap mrk. as
	shown	<u>.</u> ., _	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		, , , , , , , , , , , , , , , , , , ,	,		S33
	From wh	nich:					{	E 1/64 S4 5612S
			s S06°E, 12.0 ft. Iarch bears N23°			S33BT".		1981
	Bearings	taken to c	oster to a 4" pir enter of tree, di iround Bt's, and	stance meas	ured to nail		of tree.	
II.						round, firm	nly set with	n a 3 1/4 in. diam.
	aluminum cap marked as shown above, from which: A pine snag, bears S6°E, 12.0 ft. dist., mkd. X BT. A larch, 11 ins. diam, bears N23°W, 29.3 ft. dist., mkd. with a healed face.							
III.		iarch, ii ins ned 1 new bi		23 W, 29.3 N	aist., mka	i. With a n	edied face.	•
	A larch, 13 ins. diam, bears S40°W, 37.2 ft. dist., mkd. WE 1/64 S4 BT.							
	Monume	nt and Bear		Set a 6 ft.	galvanized s	steel guard		ned Land Survey . South and East,
							·	
	Survey (Magnetic	declination:	5/8/2008 Boyer, Tom Hom : 20° East assur ind compass and	ned	e			
	U.S. For	est Service,	Supervisiors Offi	ce, 31374 H	wy. 2, Libby	, MT 5992		
			1			ı, <u>Jhys</u> ı ce rtify /the	mas M. H	OFFICATION OMME! 10800LS we herely is true and correct.
			28/23			(flex	_	round Parky Chief
						certify that	Ven A. Bo this Comer Re by me or under Recordation A	cord correctly represents work in 20,702-101, et seq., M.C.A.)
			540th 12.0			4	Signature of Su	u \ 9750is / 9
ETC	H OF CO	ORNER 6	8	NOT	T TO SCALE	l	<u>/2009</u> Reg. U. S. For	est Service
Off	ice of Cler	k and Record	er, County of	_incoln				Sec. 33***********************************
			230216 BOO	K: CCR CCER	'S PAGE:	11734 Pa	ges: 1	
	,		STATE OF MONTA RECORDED: 12/1	-		g		
			RECORDED: 12/1 TAMMY D. LAUER			$\tilde{\mathcal{L}}$	<i>u</i>	
			FEE: \$0.00 To: Filed ,	BY:	Eaure	Leur	rev L	
		Cro	-	Z-11.5	т. 3 <mark>3</mark> N. _{R.}	34W.	<i>pcely</i> P.M., MT	

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

• corner this sheet