

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner: 4 HES 750, Section 17 T. 34N. R. 34W. P.M.M. Lincoln County

1917 GLO Record: Set a small stone, marked with a cross (x) under a quartzite stone, 26 ins. x 14 ins. x 6 ins., 16 ins. in the ground, marked "4HES750" on West face and a cross (x) on top for exact corner point, from which:

A Red fir, 9 ins. dia., bears N39°15'E, 19 lks (12.5 ft.), marked with a cross and scribed "4HES750BT"

A Red fir, 8 ins. dia., bears S71°15'E, 35 lks (23.1 ft.), marked with a cross and scribed "4HES750BT"

Raise a mound of earth, 4 ft. base, 2 ft. high, West of corner.

2010 Found: We find a stone monument, 5 ins. x 18 ins., 0.7 ft. above ground, marked "4HES750" on the westerly face from which:

A Douglas fir snag, 17 ins. dia., bears N40°E, 12.2 ft., with an overgrown heel blaze and an "X" scar.

A Douglas fir snag, 8.5 ins. dia., bears S72°30'E, 24.3 ft., scribed "4HES750RM2" with an "X" scar.

2010 Perpetuation: Establish new bearing trees as follows:

A Cedar, 9.5 ins. dia., bears S46°30'E, 16.5 ft., scribed "4HES750RM1"

A Hemlock, 8 ins. dia., bears N7°W, 16.9 ft., scribed "4HES750RM2"

Bearing trees affixed with BT tags, LSM signs, snow blazed and painted red bands.

Steel spikes driven into BT's, side center at point of measurement.

We set a galvanized steel post, N37°30'E, 1.5 ft. from monument, with LSM and USFS boundary decals.

See back side for corner exhibit

<p style="text-align: center; font-size: 1.2em;">Found Stone</p> <p style="text-align: center; font-weight: bold; margin-top: 20px;">SKETCH OF CORNER</p>	<p style="text-align: center; font-weight: bold;">CERTIFICATION</p> <p>I, <u>Keith Brandt</u> certify the information shown herein is true and correct. <i>Keith Brandt</i> _____ Signature Ground Party Chief</p> <p>I, <u>Ken E Jenkins</u> certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22101, et seq.) <i>Ken E Jenkins</i> _____ Signature of Surveyor &amp; Seal</p> <p>Date: <u>11/2010</u> Reg. No. <u>9330.LS</u> Employer: <u>Montana Northwest Company</u> <u>P.O. Box 8777, Missoula, MT 59807</u> <u>406-721-4033 Project No. 1617-10</u></p>
---	---


Sec. 17

Office of Clerk and Recorder, County of \_\_\_\_\_ This "corner

record" was filed for record on 231920 BOOK: CCR CC&R'S PAGE: 11863 Pages: 2

was noted on the cross-index plat STATE OF MONTANA LINCOLN COUNTY  
RECORDED: 03/31/2011 10:38 KOI: CC&R'S

book No. \_\_\_\_\_ TAMMY D. LAUER CLERK AND RECORDER  
FEE: \$0.00 BY: *Tammy D. Lauer*  
TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA  
County Official



● - Corner this sheet

