

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner: 5 HES 749, Section 17 T. 34N. R. 34W. P.M.M. Lincoln County

1917 GLO Record: Set a small stone, marked with a cross (x) under a quartzite stone, 25 ins. x 8 ins. x 6 ins., 15 ins. in the ground, marked "5HES749" on South face and a cross (x) on top for exact corner point, from which:

A Larch, 12 ins. dia., bears N88°15'W, 95 lks (62.7 ft.), marked with a cross and scribed "5HES749BT"

A Larch, 18 ins. dia., bears N13°W, 19 lks (12.5 ft.), marked with a cross and scribed "5HES749BT"

Raise a mound of stone, 4 ft. base, 2 ft. high, south of corner.

2010 Found: We find a stone monument, 6 ins. x 8 ins., 1.2 ft. above ground, marked "5HES749" on the South face from which:

A Larch, 19 ins. dia., bears N88°W, 62.6 ft., with an overgrown heel blaze and an "X" blaze. BT tag dated 1962.

A Larch stump, 25 ins. dia., bears N7°30'W, 12.5 ft., visible scribing "5HES" and an "X" blaze.

2010 Perpetuation: Establish new bearing trees as follows:

A Douglas fir, 10 ins. dia., bears N89°E, 39.1 ft., scribed "5HES749RM1"

A Larch, 18 ins. dia., bears N52°30'W, 21.7 ft., scribed "5HES749RM2"

Bearing trees affixed with BT tags, LSM signs, snow blazed and painted red bands.

Steel spikes driven into BT's, side center at point of measurement.

We set a galvanized steel post North, 0.5 ft from monument, with LSM and USFS boundary decals.

See back side for corner exhibit

Found Stone

SKETCH OF CORNER

CERTIFICATION

I, Keith Brandt
certify the information shown herein is true and correct.

Keith Brandt
Signature Ground Party Chief

I, Ken E Jenkins
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Ken E Jenkins
Signature of Surveyor & Seal

Date: 1/2011 Reg. No. 9330 LS

Employer: Montana Northwest Company

P.O. Box 8777, Missoula, MT 59807

406-721-4033 Project No.1617-10

Sec. 17

Office of Clerk and Recorder, County of _____ This "corner

record" was filed for record of 231921 BOOK: CCR CC&R'S PAGE: 11864 Pages: 2was noted on the cross-index | STATE OF MONTANA LINCOLN COUNTYbook No. _____ RECORDED: 03/31/2011 10:39 KOI: CC&R'S_____ TAMMY D. LAUER CLERK AND RECORDER_____ FEE: \$0.00 BY: Heather Deane_____ TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA

County Official

Cross Index No. 5 HES 749 T. 34N R. 34W PMM

● - Corner this sheet

● - Corner this sheet

STATE LINE
MONUMENT
NO. 28

N.F.S.L.

2 & CC

UNSURVEYED SEC. 8

IDAHO
MONTANA

N.F.S.L.

HES 750
PRIVATE

UNSURVEYED SEC. 17

STATE LINE
MONUMENT
NO. 29 & COR.
1 HES 750

STATE LINE

HES 113
PRIVATE

N.F.S.L.

HES 749
PRIVATE

2 & CC

N.F.S.L.

N.F.S.L.

UNSURVEYED SEC. 20

STATE LINE
MONUMENT
NO. 30

